



## 2017 Ford F550 4 x 4

## Terex Hi-Ranger LT40 40' Aerial Device

### Chassis Specifications

Engine  
6.7L 4V OHV Power Stroke V8 Turbo Diesel  
Transmission  
TorqShift 6-Speed Automatic w/PTO  
Provision  
Front Axle  
4.10 Limited Slip Ratio  
Mono-Beam W/Non-Independent  
With anti-roll bar, HD Shocks  
19.5 Painted Argent Steel Wheels  
225/70Rx19.5G BSW A/S Tires  
Rear Axles  
4.10 Limited Slip Ratio  
Shock Absorbers  
19.5 Painted Argent Steel Wheels  
225/70Rx19.5G BSW A/S Tires Payload Plus  
Upgrade Package  
Brakes  
4 Wheel Power Disc Brakes W/ Anti-Lock  
Brake System Hydro Boost (DRW)  
Fuel Tank  
40 Gallon Aft. Axle Tank  
GVWR:  
18,000  
Chassis Features  
Reg Cab  
Oxford White Paint  
Vinyl 40/20/40 Seat  
AM/FM Stereo W/ Clock  
Bumper: Black Painted Steel W/ (2) Tow  
Hooks  
Instrument Panel W/ Upfitter Switches Power  
Equipment Group  
Air Conditioned  
XL Trim  
Tele T T Mirror-PWR  
Molded Black Step  
Oxford White  
Steering Wheel Audio Controls  
Electric Brake Controller

### 132" Line Body

#### Body Specifications

12 Ga. Treadplate Wheel Wells  
16 Ga. Body Materials  
12 Ga. Treadplate Floor  
12 Ga. Treadplate Compartment Tops  
Automotive Rotary Type Door Latches  
Stainless Steel Rod Door Hinges  
  
Brass Socket Type  
Chain Stops on All Doors  
Double Panel Body Doors  
Rubber Rolled Crown Type Fenders  
Master Door Lock System  
Automotive Bulb Type Weather  
Stripping Front Bulkhead  
Streetside Compartmentation:  
Bin 1 Driver Side - 30" W X 16" deep X  
40" T Bin 2 Driver Side - 24" X 16" X  
40" Vertical Bin - 54" X 16" X 18"  
Bin 4 Driver Side - 24" X 16" X 40"  
Curbside Comaprtmentation:  
Bin 1 Passenger Side - 30" W X 16" deep  
X 40" T  
Bin 2 Passenger Side - Steps  
Vertical Bin - 54" X 16" X 18"  
Bin 4 Passenger Side - 24" X 16" X 4  
  
Frame Installation  
Frame & Floor  
Tailshelf: Treadplate 30" L x 94" W  
Bumper: Recessed 2-Section  
10" L x 94" W  
Wheel Chock Storage  
Grab Handles

### Aerial Device Specifications

Working Height - 45'6"  
Lower Controls - Individual Levers @ Turntable  
Lower Boom - Filament Wound High Strength Fiberglass Insert  
Providing Insulation Gap  
Upper Boom - Filament Wound High Strength Fiberglass Boom  
Providing Insulation Gap  
Boom Rest w/ Ratchet Style Tie Down  
Rotation Self-Locking Worm Gear Rotation Drive Provided And  
Equipped With Bi-Directional Motor.  
Continuous Unrestricted Rotation  
Rated for 46KV Category C Machine in Accordance w/  
ANSI/SIA A92.2-2009  
Full Pressure Open Center Hydraulic System  
Powder Coat Painted White  
Two Complete Service Manuals  
Warning Decals  
Pedestal w/ 20 Gallon Integral Tank  
24" x 30" x 42" End Mounted Platform w/ (1) Access Step  
w/ Non-Slip Surface  
Safety Harness and Lanyard  
Insulated Platform Liner Tested at 50KV AC  
Waterproof Platform Cover  
Auxiliary Power  
Boom Tip w/ 4-Function Controls and Platform Rotator  
Upper Controls - "Control Plus" Single Stick Controller  
Platform Rated @ 400 lbs  
Hydraulic Platform Rotator  
Hydraulic Platform Tilt @ Lower Control  
Hydraulic Tool Outlets @ Platform  
Engine Stop/Start Controlled At Platform And Lower Controls

Sale Price: \$108,426.00

Outrigger Option: \$117,908.00

Price Includes Delivery to Kyle, TX

